

|                  |  |                                                       |                                                                   |
|------------------|--|-------------------------------------------------------|-------------------------------------------------------------------|
| Substrate        |  | DIN 60001                                             | min. 80 % recycled polyester                                      |
| Weave            |  | DIN ISO 9354                                          | woven fabric                                                      |
| Weight approx.   |  | DIN EN ISO 2286-2                                     | 260 g/m <sup>2</sup>                                              |
| Fire retardancy  |  | DIN 4102 B1, B-s3,d0, NFPA 701, Class A - ASTM E84-20 | yes                                                               |
| Application      |  | IN                                                    | indoor                                                            |
| Width            |  | DIN EN ISO 2286-1                                     | max. 510 cm / 201 inch (see overview)                             |
| Print side       |  |                                                       | width < 3 m: print side outside<br>width > 3 m: print side inside |
| Roll length      |  |                                                       | 30 - 50 ± 0,5 m                                                   |
| Care instruction |  | DIN EN 12956                                          | scrub resistant (grade 5) according to instruction*               |
| Type of ink      |  |                                                       | all kinds of solvent inks, UV-curable inks**, latex inks          |

## Advantages

- matt surface
- available in large width
  - no curling
  - dirt repellent
- opaque
- trimming cold (no fraying)

## Applications

- roll up
- banner
- frontlit
- frame tensioning systems
- art reproduction
- wall covering\*\*\*

Classified as Type II - Category V in accordance to ASTM F793/793M-15 \* please have a look at the cleaning instructions on [www.jm-mediatex.com](http://www.jm-mediatex.com)

\*\* please consider the risk of curling because UV-curable inks will still be hardening after a while

\*\*\* please test in advance; the adhesive behavior depends on the surface applied

All details are nominal values and are subject to change within usual tolerances (± 5 %). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 06/2022

