

Substrate		DIN 60001	100 % polyester
Weave		DIN ISO 9354	woven fabric
Weight approx.		DIN EN ISO 2286-2	220 g/m ²
Fire retardancy		DIN 4102 B1, ÖNORM A3800, M1, NFPA 701, CA 1237	yes
Application			indoor, outdoor (short-term)
Width		DIN EN ISO 2286-1	max. 510 cm / 201 inch (see overview)
Print side			width < 3 m: print side outside width > 3 m: print side inside
Roll length			30 - 50 ± 0,5 m
Care instruction		DIN EN 12956	scrub resistant (grade 5) according to instruction*
Type of ink			all kinds of solvent inks, UV-curable inks, latex inks**

Advantages

- matt surface
- available in large width
- canvas like fabric
 - easy to clean
 - dirt-repellent
 - trimming cold (no fraying)

Applications

- roll up
- banner
- frontlit
- frame tensioning systems
- art reproduction
- wall covering***

* please have a look at the cleaning instructions on www.jm-mediatex.com

** not for outdoor use

*** please test in advance; the adhesive behavior depends on the surface applied

made in Germany

All details are nominal values and are subject to change within usual tolerances (± 5 %). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 01/2020